

EUROPEAN PATENT OFFICE

Patent Abstracts of Japan

PUBLICATION NUMBER : 2000188296
PUBLICATION DATE : 04-07-00


APPLICATION DATE : 22-12-98
APPLICATION NUMBER : 10365595

APPLICANT : SONY CORP;

INVENTOR : KANEMATSU SHIGERU;

INT.CL. : H01L 21/331 H01L 29/73 H01L 21/8222
H01L 27/06 H01L 21/8249

TITLE : SEMICONDUCTOR DEVICE AND ITS
MANUFACTURE



ABSTRACT : PROBLEM TO BE SOLVED: To reduce leakage current caused by a parasitic transistor and, at the same time, to improve the emitter current utilization efficiency of a horizontal PNP bipolar transistor in a semiconductor device having the transistor.

SOLUTION: After an N+ embedded layer 2 and a first impurity diffusion layer 15 are formed in a silicon substrate (P-sub) 1, the impurity contained in the layer 15 is diffused into an N-epi layer 3 overlaying the layer 15 through heat treatment and, at the same time, brought into contact with the bottom of the LOCOS Ox 4 of an element separating film. In addition, an N+ sinker layer 6 which is connected to the first impurity diffusion layer 15 through a base, a collector diffusion layer, and the N-epi layer 3 is formed on the N-epi layer 3. Therefore, the occurrence of leakage currents can be reduced and, at the time time, the emitter current utilization efficiency of a horizontal PNP bipolar transistor can be improved by eliminating the parasitic transistor structure resulting from the structure of the bipolar transistor.

COPYRIGHT: (C)2000,JPO

BEST AVAILABLE COPY